



BN International BV
P.O Box 2 ; 1270AA Huizen ; The Netherlands
Tel. : 0031-35 5248439
Fax.: 0031-35 5234196
Mail: wallcovering@bnint.nl
Web.: www.bnwallcoverings.com

Productsheet

| Specifications | "Aqua" Non-woven vinylwallcovering | | |
|---|--|--------------------|--------------------------------|
| | <u>Dimensions</u> | <u>Standard</u> | |
| Date | : 21-01-2016 | | |
| Application | : Wallcovering. | | |
| Type | : Vinyl coating on a non woven backing. | | |
| <u>Packing</u> | : Each roll in shrinkfoil, 12 roll per cartonbox. | | |
| Width of the roll | : 53 | cm. | |
| Roll length | : 8,40 | mtr | |
| <u>Composition</u> | | | |
| Total weight | : 355 ± 35 | # g/m ² | BN method 4200 |
| Basematerial | : 85 - 90 ± 5 | # g/m ² | |
| Coating | : 265 | # g/m ² | |
| Basematerial | : Non woven | | |
| Coating | : Foamed PVC. | | |
| # = Depends on design | | | |
| <u>Other properties</u> | | | |
| <u>Flammability</u> | : European Class : B-s2 -d0 | | EN 13501-1 |
| <u>Lightfastness</u> | : ≥ 7 international wooscale | | BS1006; ISO 105-B02; DIN 54004 |
| <u>Washability</u> | : Washable/ Scrubbable (*) (*) depends on design/structure. | | EN 233 / EN 12956 |
| <u>Strippability</u> | : Strippable / Peelable. | | |
| <u>Resistance against chemical influences</u> | | | |
| Resistant to | : Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids. | | |
| Not resistant to | : Solvents like Ketones; Esters; Aromatic hydrocarbons. | | |
| <u>Application</u> | | | |
| Wall | : Dry, solid and free of grease | | |
| Hanging | : See roll label | | |
| Adhesive | : Methylan special for non woven or similar | | |